

# MDSM-22S Fatigue Camera



## Product Specification



<b>Key features</b>	<p>Compact and simple to install</p> <p>Minimal obstruction for driver's view</p> <p>Built-in Speaker</p> <p>Designed to protect the driver with timely alerts for:</p> <p>DDAW features</p> <ul style="list-style-type: none"> <li>- Drowsiness (eyes closing)</li> <li>- Yawning</li> </ul> <p>Complies with the requirements of the EU 2019/2144 DDAW regulation</p>	<b>Package contents</b> <ul style="list-style-type: none"> <li>1 x MDSM-22S Camera</li> <li>1 x MDSM-22S Main Control Box</li> <li>1 x Main Cable</li> <li>1 x Power Cable</li> <li>1 x CAN Cable</li> <li>1 x 3M Tape (Camera)</li> <li>1 x L-Shaped Hex Wrench</li> <li>1 x Cradle Neck T2 (For Buses &amp; Trucks) (Fitted)</li> <li>1 x Cradle Neck T1</li> <li>1 x Camera fixing screw</li> <li>2 x Control Box fixing screw</li> <li>User Manual</li> </ul>
---------------------	---	---

<b>Dimensions / Weight</b>	Camera body excl. cable and bracket	49.3 x 40.68 x 56.15mm / 244g inc. cable
	Control Box	80.8 x 148 x 27mm / 127g
<b>OS</b>	Embedded Linux	
<b>CPU</b>	ARM Cortex A7 Quad-Core@1.1GHz	
<b>Memory</b>	512MB NAND Flash, 1GB DDR3	
<b>Power Input</b>	12V to 32V DC	
<b>DSM Camera</b>	88 degree, HD	
<b>Interface</b>	CAN	
<b>SD Card</b>	Up to 128GB, format free (Optional)	
<b>Temperature</b>	Operating	-20°C to 70°C (-4°F to 158°F)
	Storage	-40°C to 85°C (-40°F to 185°F)